

Technical Data Sheet

DT2GPB

Physical Data

Product	DT2GPB (Digi-tac2000)
Description	PVC (120μ) with solvent adhesive, 2PE liner (monomeric)
Material	PVC
Finish	Gloss
Basic weight	165gsm/m ± 5%
Thickness(Face film)	0.12mm ± 0.005mm
Liner thickness	0.14mm (80gsm 2PE)
Adhesive-pressure sensitive	Permanent / Grey / Solvent
Adhesive thickness	0.028mm
Total thickness	0.288mm ± 0.005mm
Total weight	330 gsm/m2 ± 5%
Available roll sizes	1370mm x 50m / 1524mm x 50m
Core size	3 inch

Physical & Chemical Property	standard	unit	specs.
Ball Tack	J.DOW method	Ball	19
180° Peel Adhesion	PSTC # 1	Kg / Inch	1.1 ↑
90° Release Force			15 ± 5
0° Holding Power	PSTC # 7	Inch / Hr	72 ↑
Tensil Strength		g/10mm	1500 ↑
Elongation		%	150 ↑
Shrinking	80°C *48HR		0.5 ↓
Heat Resistance		° C	80
Cold Resistance		° C	5
Storage Condition		° C & Humidity	5°C ~ 40°C & 30% ~ 70%
Storage Validity		Year	1

Durability

Up to 3 years outdoor

